

# Liquid Tight Fittings

## Liquid Tight Connectors, 90°




90° connector for use with metallic and nonmetallic "Type B" liquid tight conduit.

NPT Threads. Polyethylene gasket. NEMA TYPE 2,3,3R,4 &12.

Suitable for use in Class 1 Division 2, - Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC 501.30 (B)

 File No. E9391

 File No. LR39354

### Die Cast Zinc

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
469-LT2	3/8"	25	100
470-LT2	1/2"	25	100
471-LT2	3/4"	10	50
472-LT2	1"	5	25
473-LT2	1 1/4"	5	25

### Die Cast Zinc / Insulated Throat - 105°C

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
469-LTI2	3/8"	25	100
470-LTI2	1/2"	25	100
471-LTI2	3/4"	10	50
472-LTI2	1"	5	25
473-LTI2	1 1/4"	5	2

### Cast Zinc


Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
474-LT2	1 1/2"	2	10
475-LT2	2"	---	5
476-LT2	2 1/2"	---	1
477-LT2	3"	---	1
478-LT2	3 1/2"	---	1
479-LT2	4"	---	1

### Cast Zinc / Insulated Throat - 105°C

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
474-LTI2	1 1/2"	2	10
475-LTI2	2"	---	5
476-LTI2	2 1/2"	---	1
477-LTI2	3"	---	1
478-LTI2	3 1/2"	---	1
479-LTI2	4"	---	1

## Zinc

### Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 9/16

Dimension B in Inches: 2

Dimension C in Inches: 2-1/2

### Application

90 Degree connector for use with metallic and nonmetallic "Type B" liquid tight conduit. 1" and up cast zinc.

### Product Information

Material: Zinc Cast

Finish: Zinc electro-plate

### Certifications & Codes:

CSA File Number: LR39354

Federal Specification Number: A-A-50552

NEMA Standard: FB-1

UL File Number: E9391

UL Standard: UL-514B

UNSPSC: 39121420

**Catalog ID:** 472-LT2

**UPC Number:** 781747154729

**Description:** Connector, Liquid Tight, 90 Degree, Cast Zinc, Size 1 Inch

**Application:** 90 Degree connector for use with metallic and nonmetallic "Type B" liquid tight conduit. 1" and up cast zinc.

**Trade Size:** 1"

**Std Pkg Qty:** 25

**Unit Qty:** 5